

YAKUN

Yakun R5 Pro Tiefeinsteiger



ice

SPEZIFIKATIONEN / SPECIFICATIONS

Motor	Bosch Performance CX Smart System, 250W, 85Nm, 25km/h
Display	Bosch Kiox 300 + LED Remote
Akku / Battery	Bosch PowerTube 750Wh
Ladegerät / Charger	Bosch Standard Charger 4A

750 Wh	BOSCH	27,5"	StVZO	150 Kg
--------	-------	-------	-------	--------

Rahmen / Frame	aluminium 6061, disc brake Post Mount
Gabel / Fork	RockShox Recon RL, air, Travel: 80mm, Aluschaft 1 1/8 - 1 1/2" tapered, thru-axle Boost
Schaltwerk / Rear derailleur	Shimano Nexus, 5-speed /
Schalthebel / Shift lever	Shimano Nexus, twist shifter
Zahnkranz (hinten) / Sprocket	Gates sprocket, 32 teeth
Kette / Chain	Gates CarbonDrive
Bremshebel / Brake lever	Shimano XT T8100, aluminium
Bremse vorne / Brake front	Shimano Deore XT M8120, 203mm
Bremse hinten / Brake rear	Shimano Deore XT M8120, 180mm
Reifen vorne / Tyres front	Schwalbe Al Grounder Performance, 60-584, reflex
Reifen hinten / Tyres rear	Schwalbe Al Grounder Performance, 60-584, reflex
Felgen vorne / Rims front	Schürmann Yak25, eyed, double-walled rim, aluminium
Felgen hinten / Felgen rear	Schürmann Yak25, eyed, double-walled rim, aluminium
Vorderradnabe / Front wheel hub	Shimano MT400-B
Hinterradnabe / Rear wheel hub	Shimano Nexus
Speichen / Spokes	Sapim Leader, black
Lenker / Handlebar	Ergoriser, oversize 720mm
Griffe / Grips	Herrmans Click Ergo - lock on grips
Vorbau / Stem	aluminium, angle ajustable, A-head, Bar bore: 31.8mm
Steuersatz / Headset	A-Head Tapered
Sattel / Saddle	Selle Royal VivoErgo
Sattelstütze / Seat post	Dropper-Post Remote, telescope, 34.9mm, aluminium
Pedale / Pedals	VP 625 aluminium, non-slip
Scheinwerfer / Headlight	Litemove AE-130, 130 lux
Rücklicht / Rear light	Spanninga Pimento
Dynamo / Dynamo	via system battery
Gepräckträger / Carrier	Winora system carrier, MIK
Schutzbleche / Fenders	Curana Apollo 65, aluminium
Ständer / Stand	Ursus Power 94, adjustable
Zul. Gesamtgewicht / Permitted total weight	150kg
Fahrradtyp / Bicycle type	City, Trekking, Cross

Yakun R5 Pro Tiefeinsteiger 27.5"

27.5"	45	44076245	ice
27.5"	50	44076250	ice
27.5"	55	44076255	ice
27.5"	60	44076260	ice